

	<b>PRODUCT SPECIFICATION</b>	Rev.	1.0
		Date	2012.04.02
<b>Li202SX-7800 (Rechargeable Li-ion Battery Pack 3P3S, 7800mAh)</b>		Page	Sheet 1 of 3

## SPECIFICATION OF PRODUCT

**Rechargeable Li-ion Battery Pack**  
**Model : Li202SX-7800 (10.8V, 7800mAh)**

### ENERTECH INTERNATIONAL, INC.

710-3, Yongtan-Dong , Chung-Ju , Chung-buk , Korea  
 TEL: 82-43-850-1840 / 82-2-3457-8650    FAX: 82-2-564-3566

[www.enertechint.com](http://www.enertechint.com)

**1. Descriptions**

1.1 Description Rechargeable Lithium ion battery pack

1.2 Battery Cell Configuration 3P-3S

**2. Electrical specification(@25 °C)**

Item	Specification	Remarks
2.1 Capacity	7800mAh	Nominal (by standard charge and discharge)
	7500mAh	Minimum
2.2 Voltage	10.8V	Nominal
2.3 Charging method	CC-CV	Constant-voltage with limited current
2.4 Charging voltage	12.6±0.05V	
2.5 Charging current	3900mA	Standard
2.6 Charging current cut-off	< 390mA	
2.7 Discharging current	1560mA	Standard
	3900mA	Continuous
	6000mA	Peak discharge less than 5s
2.8 Discharge cut-off voltage	9.0V	
2.9 Internal resistance	< 300mΩ	
2.10 Operating temperature	0 to 40°C	Standard charge
	-20 to 55°C	Standard discharge
2.11 Storage temperature	0 ~ 25°C	≤ 1 Year
	0 ~ 45°C	≤ 3 Months
	0 ~ 60°C	≤ 1 Month
2.12 Storage humidity	20 ~ 85 % RH	Not condensed
2.13 Smart Module Communication	SMBus	Type
	V1.1	Revision

**3. Safety specification**

Item	Remarks	Specification
3.1 Over charge	Prohibition	4.35V±50 mV/Cell
	Release	4.05V±100 mV/Cell
	Delay time	< 1.0sec.
3.2 Over discharge	Prohibition	2.40V±80 mV/Cell
	Release	2.70V±100 mV/Cell
	Delay time	< 1.0sec.
3.3 Over current	Prohibition	10 ~ 16A (Depend on cell voltage)
	Release	by charging
3.4 Power dissipation	Operating	< 300uA
	Shut down	< 30uA

**4. Physical specification**

Item	Remarks	Specification
3.1 Dimension	L x W x H	140.0±0.5 x 88.8±0.5 x 19.6±0.3
3.2 Terminal (Output)		Power(+),Clock(C),Data(D),Thermistor(T),Power(-)
3.3 Weight		< 450g

**5. Certification : UL (No. : MH29843)**

This drawing is property of Enertech International, Inc. Use or copy of this drawing without proper permission from the appropriate technical-document managing department is prohibited.

