	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB426395(Rechargeable Lithium Ion Battery)		Page	1 / 3


SPECIFICATION OF PRODUCT

Rechargeable Lithium Ion Battery
Model : SPB426395
(Grade : A1)

ENERTECH INTERNATIONAL, INC.

269, Chungjuhosu-ro, ChungJu-city, Chungbuk , Korea
 TEL: 82-43-850-1950 FAX: 82-43-855-9175
www.enertechint.com

	Issued	Checked	Approved
ENERTECH INTERNATIONAL, INC.	<div style="border: 2px solid blue; padding: 5px; display: inline-block;"> Electronic Approval </div>		
Date			

	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB426395(Rechargeable Lithium Ion Battery)		Page	2 / 3

1. Scope


This specification defines the characteristics of a rechargeable lithium ion battery manufactured by **ENERTECH INTERNATIONAL INC.**

2. Description and Model

- 2.1 Description Cell (Rechargeable Lithium ion Battery)
2.2 Model SPB426395

3. Nominal Specifications

Item		Specification
3.1 Nominal Capacity		2400 mAh(0.2C discharge)
3.2 Energy density	Volumetric	353 Wh/L
	Gravimetric	189 Wh/Kg
3.3 Nominal Voltage		3.7V
3.4 Operating Voltage Range		3.00V ~ 4.20V
3.5 Standard	Charge Current	1200mA (0.5C)
	Discharge Current	480mA (0.2C)
3.6 Maximum	Charge Current	2400mA (1.0C)
	Discharge Current	4800mA (2.0C)
3.7 Operating Temperature	Charge	0°C ~ 45°C
	Discharge	-20°C ~ 60°C
3.8 Storage Temperature	0°C ~ 25°C	≤ 1 Year
	0°C ~ 40°C	≤ 3 Month
	-10°C ~ 50°C	≤ 1 Month
3.9 Storage Humidity		45~85%RH
3.10 Cell size	Thickness	4.2 +0.2/-1.0mm (Initial fully charged Cell)
	Width	63.0 +0.0/-4.0mm
	Length	95.0 +2.0/-1.0mm
3.11 AC Impedance		Max. 20mΩ
3.12 Weight		Max. 47.0g

	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB426395(Rechargeable Lithium Ion Battery)		Page	3 / 3

◆ **Out view drawing for SPB426395**

