	<b>SIMPLIFIED SPECIFICATION</b>	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
<b>SPB463048(Rechargeable Lithium Ion Battery)</b>		Page	1 / 3

# SPECIFICATION OF PRODUCT

**Rechargeable Lithium Ion Battery**

**Model : SPB463048**

**(Grade : A1)**


## ENERTECH INTERNATIONAL, INC.

269, Chungjuhosu-ro, ChungJu-city, Chungbuk , Korea

TEL: 82-43-850-1950 FAX: 82-43-855-9175

[www.enertechint.com](http://www.enertechint.com)

	Issued	Checked	Approved
<b>ENERTECH INTERNATIONAL, INC.</b>	<div style="border: 2px solid blue; padding: 5px; display: inline-block;"> <b>Electronic Approval</b> </div>		
Date			

	<b>SIMPLIFIED SPECIFICATION</b>	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
<b>SPB463048(Rechargeable Lithium Ion Battery)</b>		Page	2 / 3

## 1. Scope

This specification defines the characteristics of a rechargeable lithium ion battery manufactured by **ENERTECH INTERNATIONAL INC.**


## 2. Description and Model

2.1 Description           Cell (Rechargeable Lithium ion Battery)

2.2 Model                 SPB463048

## 3. Nominal Specifications

Item		Specification
3.1 Nominal Capacity		700 mAh(0.2C discharge)
3.2 Energy density	Volumetric	391 Wh/L
	Gravimetric	192 Wh/Kg
3.3 Nominal Voltage		3.7V
3.4 Operating Voltage Range		3.00V ~ 4.20V
3.5 Standard	Charge Current	350mA (0.5C)
	Discharge Current	140mA (0.2C)
3.6 Maximum	Charge Current	700mA (1.0C)
	Discharge Current	1400mA (2.0C)
3.7 Operating Temperature	Charge	0°C ~ 45°C
	Discharge	-20°C ~ 60°C
3.8 Storage Temperature	0°C ~ 25°C	≤ 1 Year
	0°C ~ 40°C	≤ 3 Month
	-10°C ~ 50°C	≤ 1 Month
3.9 Storage Humidity		45~85%RH
3.10 Cell size	Thickness	4.6 +0.2/-0.4mm (Initial fully charged Cell)
	Width	30.0 ± 1.0 mm
	Length	48.0 ± 1.0 mm
3.11 AC Impedance		Max. 50mΩ
3.12 Weight		Max. 13.5g

	<b>SIMPLIFIED SPECIFICATION</b>	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
<b>SPB463048(Rechargeable Lithium Ion Battery)</b>		Page	3 / 3

◆ **Out view drawing for SPB463048**

