	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB503759(Rechargeable Lithium Ion Battery)		Page	1 / 3

SPECIFICATION OF PRODUCT

Rechargeable Lithium Ion Battery

Model : SPB503759

(Grade : A2)


ENERTECH INTERNATIONAL, INC.

269, Chungjuhosu-ro, ChungJu-city, Chungbuk , Korea

TEL: 82-43-850-1950 FAX: 82-43-855-9175

www.enertechint.com

	Issued	Checked	Approved
ENERTECH INTERNATIONAL, INC.	<div style="border: 2px solid blue; padding: 5px; display: inline-block;"> Electronic Approval </div>		
Date			

	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB503759(Rechargeable Lithium Ion Battery)		Page	2 / 3

1. Scope


This specification defines the characteristics of a rechargeable lithium ion battery manufactured by **ENERTECH INTERNATIONAL INC.**

2. Description and Model

2.1 Description	Cell (Rechargeable Lithium ion Battery)
2.2 Model	SPB503759

3. Nominal Specifications

Item		Specification
3.1 Nominal Capacity		1330 mAh(0.2C discharge)
3.2 Energy density	Volumetric	451 Wh/L
	Gravimetric	205 Wh/Kg
3.3 Nominal Voltage		3.7V
3.4 Operating Voltage Range		3.00V ~ 4.20V
3.5 Standard	Charge Current	665mA (0.5C)
	Discharge Current	266mA (0.2C)
3.6 Maximum	Charge Current	1330mA (1.0C)
	Discharge Current	2660mA (2.0C)
3.7 Operating Temperature	Charge	0°C ~ 45°C
	Discharge	-20°C ~ 60°C
3.8 Storage Temperature	0°C ~ 25°C	≤ 1 Year
	0°C ~ 40°C	≤ 3 Month
	-10°C ~ 50°C	≤ 1 Month
3.9 Storage Humidity		45~85%RH
3.10 Cell size	Thickness	5.0 +0.0/-0.4mm (Initial fully charged Cell)
	Width	37.0 ± 1.0mm
	Length	59.0 ± 1.0mm
3.11 AC Impedance		Max. 30mΩ
3.12 Weight		Max. 24.0g

	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB503759(Rechargeable Lithium Ion Battery)		Page	3 / 3

◆ **Out view drawing for SPB503759**

