	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB503759a(Rechargeable Lithium Ion Battery)		Page	1 / 3

SPECIFICATION OF PRODUCT

Rechargeable Lithium Ion Battery

Model : SPB503759a

(Grade : A3)


ENERTECH INTERNATIONAL, INC.

269, Chungjuhosu-ro, ChungJu-city, Chungbuk , Korea

TEL: 82-43-850-1950 FAX: 82-43-855-9175

www.enertechint.com

	Issued	Checked	Approved
ENERTECH INTERNATIONAL, INC.	<div style="border: 2px solid blue; padding: 5px; display: inline-block;"> Electronic Approval </div>		
Date			

	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB503759a(Rechargeable Lithium Ion Battery)		Page	2 / 3

1. Scope

This specification defines the characteristics of a rechargeable lithium ion battery manufactured by **ENERTECH INTERNATIONAL INC.**

2. Description and Model

- 2.1 Description Cell (Rechargeable Lithium ion Battery)
2.2 Model SPB503759a

3. Nominal Specifications

Item		Specification
3.1 Nominal Capacity		1300 mAh(0.2C discharge)
3.2 Energy density	Volumetric	441 Wh/L
	Gravimetric	192 Wh/Kg
3.3 Nominal Voltage		3.7V
3.4 Operating Voltage Range		3.00V ~ 4.20V
3.5 Standard	Charge Current	650mA (0.5C)
	Discharge Current	260mA (0.2C)
3.6 Maximum	Charge Current	1300mA (1.0C)
	Discharge Current	2600mA (2.0C)
3.7 Operating Temperature	Charge	0°C ~ 45°C
	Discharge	-20°C ~ 60°C
3.8 Storage Temperature	0°C ~ 25°C	≤ 1 Year
	0°C ~ 40°C	≤ 3 Month
	-10°C ~ 50°C	≤ 1 Month
3.9 Storage Humidity		45~85%RH
3.10 Cell size	Thickness	5.0 +0.2/-0.4mm (Initial fully charged Cell)
	Width	37.0 ± 1.0mm
	Length	59.0 ± 1.0mm
3.11 AC Impedance		Max. 40mΩ
3.12 Weight		Max. 25.0g

◆ Out view drawing for SPB503759a

