	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB704684(Rechargeable Lithium Ion Battery)		Page	1 / 3

SPECIFICATION OF PRODUCT

Rechargeable Lithium Ion Battery

Model : SPB704684

(Grade : A1)


ENERTECH INTERNATIONAL, INC.

269, Chungjuhosu-ro, ChungJu-city, Chungbuk , Korea

TEL: 82-43-850-1950 FAX: 82-43-855-9175

www.enertechint.com

	Issued	Checked	Approved
ENERTECH INTERNATIONAL, INC.	<div style="border: 2px solid blue; padding: 5px; display: inline-block;"> Electronic Approval </div>		
Date			

	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB704684(Rechargeable Lithium Ion Battery)		Page	2 / 3

1. Scope


This specification defines the characteristics of a rechargeable lithium ion battery manufactured by **ENERTECH INTERNATIONAL INC.**

2. Description and Model

- 2.1 Description Cell (Rechargeable Lithium ion Battery)
2.2 Model SPB704684

3. Nominal Specifications

Item		Specification
3.1 Nominal Capacity		3300 mAh(0.2C discharge)
3.2 Energy density	Volumetric	451 Wh/L
	Gravimetric	204 Wh/Kg
3.3 Nominal Voltage		3.7V
3.4 Operating Voltage Range		3.00V ~ 4.20V
3.5 Standard	Charge Current	1650mA (0.5C)
	Discharge Current	660mA (0.2C)
3.6 Maximum	Charge Current	3300mA (1.0C)
	Discharge Current	6600mA (2.0C)
3.7 Operating Temperature	Charge	0°C ~ 45°C
	Discharge	-20°C ~ 60°C
3.8 Storage Temperature	0°C ~ 25°C	≤ 1 Year
	0°C ~ 40°C	≤ 3 Month
	-10°C ~ 50°C	≤ 1 Month
3.9 Storage Humidity		45~85%RH
3.10 Cell size	Thickness	7.0 +0.2/-0.4mm (Initial fully charged Cell)
	Width	46.0 ± 1.0mm
	Length	84.0 ± 1.0mm
3.11 AC Impedance		Max. 20mΩ
3.12 Weight		Max. 60.0g

	SIMPLIFIED SPECIFICATION	Rev.	0.0
		Date of Issued	18 July. 2012
		Date of revision	18 July. 2012
SPB704684(Rechargeable Lithium Ion Battery)		Page	3 / 3

◆ **Out view drawing for SPB704684**

